



Description

Current Transformers with a ratio of $I_p/5$, for measurement devices. Ratios ranging from 200/5A to 2000/5A and a plastic case in accordance with Thermal Class E. Capable of being mounted on Busbar or flat fixed on a base the M14080 comes complete with sealable integrated terminal cover.

| Electrical Characteristics | | Mechanical Characteristics | |
|----------------------------|-------------------------|----------------------------|-----|
| 0.72 kV | Highest Voltage | Material Thermal Class | E |
| 50/60 Hz | Frequency | Integrated Terminal Cover | Yes |
| IEC 61869-1 & 61869-2 | Standard | DIN Rail Mounting | No |
| 200 - 2000 A | Primary Ratio (I_p) | Busbar / Cable Clamp | Yes |
| 1.5 - 60 VA | Burden | Mounting Feet | Yes |
| 0.2s - 1 % | Accuracy Class | Captured Terminal Screws | Yes |

| Ratio | Maximum VA @ Class | | | |
|---------|--------------------|-----------|-----------|---------|
| | Class 0.2s | Class 0.2 | Class 0.5 | Class 1 |
| 200/5A | - | - | 2.5 | 5.0 |
| 250/5A | - | - | 5.0 | 10.0 |
| 300/5A | - | 1.5 | 7.5 | 15.0 |
| 400/5A | - | 2.5 | 10.0 | 20.0 |
| 500/5A | 2.5 | 5.0 | 15.0 | 30.0 |
| 600/5A | 3.75 | 7.5 | 15.0 | 30.0 |
| 750/5A | 5.0 | 10.0 | 15.0 | 45.0 |
| 800/5A | 5.0 | 10.0 | 15.0 | 45.0 |
| 1000/5A | 10.0 | 15.0 | 30.0 | 60.0 |
| 1200/5A | 12.5 | 15.0 | 30.0 | 60.0 |
| 1250/5A | 12.5 | 30.0 | 60.0 | 60.0 |
| 1500/5A | 15.0 | 30.0 | 60.0 | 60.0 |
| 1600/5A | 15.0 | 30.0 | 60.0 | 60.0 |
| 2000/5A | 15.0 | 30.0 | 60.0 | 60.0 |