



## Description

Current Transformers with a ratio of  $I_p/5$ , for measurement devices such as ammeters, kilowatt hour meters and multi meters. Ratios ranging from 50/5A to 400/5A and a plastic case in accordance with Thermal Class E. Capable of being mounted on DIN rail (accessory required) or flat fixed on a base the M4514 comes complete with sealable integrated terminal cover.

Electrical Characteristics		Mechanical Characteristics	
0.72 kV	Highest Voltage	Material Thermal Class	E
50/60 Hz	Frequency	Integrated Terminal Cover	Yes
IEC 61869-1 & 61869-2	Standard	DIN Rail Mounting	Yes
50 - 400 A	Primary Ratio ( $I_p$ )	Busbar / Cable Clamp	No
1 - 5 VA	Burden	Mounting Feet	Yes
0.5 - 1 %	Accuracy Class	Captured Terminal Screws	Yes

Ratio	Maximum VA @ Class	
	Class 0.5	Class 1
50/5A	-	1.5
60/5A	-	1.5
75/5A	-	2.5
80/5A	1.0	2.5
100/5A	1.5	3.75
120/5A	1.5	3.75
125/5A	2.5	3.75
150/5A	2.5	5.0
200/5A	3.75	5.0
250/5A	5.0	5.0
300/5A	5.0	5.0
400/5A	5.0	5.0