



## Description

Current Transformers with a ratio of  $I_p/5$ , for measurement devices such as ammeters, kilowatt hour meters and multi meters. Ratios ranging from 600/5A to 3200/5A and a plastic case in accordance with Thermal Class E. Capable of being mounted using a busbar clamp the R113TW6 comes complete with sealable terminal cover.

Electrical Characteristics		Mechanical Characteristics	
0.72 kV	Highest Voltage	Material Thermal Class	E
50/60 Hz	Frequency	Removable Terminal Cover	Yes
IEC 61869-1 & 61869-2	Standard	DIN Rail Mounting	No
600 - 3200 A	Primary Ratio ( $I_p$ )	Busbar / Cable Clamp	Yes
1.5 - 45 VA	Burden	Mounting Feet	No
0.2 - 1 %	Accuracy Class	Captured Terminal Screws	Yes

Ratio	Maximum VA @ Class			
	Class 0.2	Class 0.5s	Class 0.5	Class 1
600/5A	1.5	3.75	5	10
800/5A	2.5	7.5	10	15
1000/5A	3.75	7.5	10	15
1200/5A	15	15	20	30
1250/5A	15	15	20	30
1500/5A	15	15	20	30
1600/5A	15	15	20	30
2000/5A	15	20	25	45
2500/5A	15	20	25	45
3000/5A	15	25	30	45
3200/5A	15	25	30	45